

DU-HA[®]

Dark Gray P/N // 20007
Light Gray P/N // 20008
Tan P/N // 20009

Installation Instructions for 2000 - 2003 Ford F-150 Supercabs

Installation Instructions:

- 1 Flip up rear seats.
- 2 Remove the jack from under the back seat (01½ - 03 trucks). Jack should be installed with an angle bracket, wing nut and seat belt or with two wing nuts. (00 - 01½ trucks have jack installed under the front seat.)
- 3 Slide the passenger side end of the DU-HA against the seat bracket. Snap the other side of the DU-HA around driver's side seat bracket. (You may have to bend side inward to snap into position.)
- 4 Re-install the jack in the same manner as removed (if applicable). If the truck came with a seat belt type fastener, insert the strap through the slot in bottom of the DU-HA and place the buckle over top of rear of the DU-HA (Note: install dividers before buckling seat belt). You may also remove the jack and jack handles from the plastic jack box and place in the DU-HA (as shown).
- 5 Secure the DU-HA to the floor of truck with jack wing nut and large washer provided.
- 6 Install the dividers by sliding them into slots in end and bottom of the DU-HA.
- 7 Install the organizer/gun racks by sliding them into the pre-cut slots in the dividers.

Safety Instructions:

Warning: Seat bottom must be latched down at all times while vehicle is moving. Make sure the DU-HA is secured in the vehicle according to installation instructions. Do not store explosives or hazardous materials in the DU-HA. Do not place loaded guns in the DU-HA.

For further instructions refer to truck owners manual or contact DU-HA, Inc.

