

Installation Instructions for 00-07 Chevrolet & GMC Heavy Duty Crew Cab (Classic) *Behind-the-Seat Storage*

Materials Needed:

- // Drill // 7/16" Socket
- // 5/16" Drill Bit // 7/16" Wrench
- // Ratchet

Installation Instructions:

- 1 Pull and recline front seats all the way forward. Flip rear seat bottom up and fold seat back down.
- 2 Set the DU-HA in truck, centered on the floor, with DU-HA lettering facing forward (as shown). Make sure slot in the DU-HA is aligned with center child safety seat bracket.
- 3 With the DU-HA centered on floor use the DU-HA as a template to mark and drill two 5/16" holes in the floor flaps. Flip up the front flap to make sure the DU-HA is positioned against the rear of the cab before drilling. If you do happen to drill through the duct below the floor flaps they are only pressure release vents for cab pressure so a hole will not affect them. It's best to secure driver's side first before drilling passengers' side.
- 4 To secure the DU-HA to the floor flaps, use included washer with a 1/4" x 1-1/2" bolt. Place bolt through DU-HA and floor flap and secure with washer and 1/4" nut. Tighten down using ratchet with 7/16" socket and a 7/16" wrench.
- 5 Secure the top of DU-HA to center child safety seat bracket using nylon strap. Thread strap through the slot in the front of the DU-HA and through the child safety seat bracket. Loop strap together by threading up through the bottom of the back slot of the buckle and down through the front slot of the buckle (as shown below). The nylon strap will help secure the DU-HA from tipping forward.
- 6 If desired, install organizer / gun racks by bending and snapping them into the slots in the DU-HA (as shown). Gun racks can be installed to hold two guns or one gun depending on how you install them.



The DU-HA bolts to rear floor flaps to allow access to the jack when tilted forward.



Ribs on buckle should face up. Thread strap through buckle as shown.



This is how the DU-HA should look installed behind the back seat.

Safety Instructions:

Warning: Seat back must be latched up at all times while vehicle is moving. Make sure DU-HA is secured in vehicle according to installation instructions. Do not store explosives or hazardous materials in the DU-HA. Do not place loaded guns in the DU-HA.

For further instructions refer to truck owners manual or contact DU-HA, Inc.

