

DU-HA Replacement Audiophile Subwoofer Box for 2004–2008 Ford F-150 SuperCrew *and* for 2006–2008 Lincoln Mark LT

Fits DU-HA Part Numbers

20004

20006


STEP 1

Materials Needed:

- // T20 Torx Bit
- // T15 Torx Bit
- // Needlenose Pliers

To Remove Factory OEM Audiophile Subwoofer:

- 1 Lift up both sides of back seat.
- 2 Remove bolts that attach subwoofer box to seat brackets. There are 2 on the driver's side and 1 on the passenger side.
- 3 Pull subwoofer box all the way out from under the seat and unplug amp.
- 4 Replace bolts in their original position on the seat brackets.
- 5 Turn Audiophile subwoofer box over and unplug the wire going into the amp by pressing button on back of plug.
- 6 Remove 4 screws from amp box using a T15 Torx and remove amp.
- 7 Remove 8 screws from the speaker using a T20 Torx.
- 8 Pull the speaker out of the box as far as possible. Apply light pressure up on the black tab under the speaker, then gently wiggle the metal plugs free from the speaker using a needlenose pliers. Remove all 4 metal connectors from the speaker. Set speaker aside.
- 9 Remove foam pad from wire.
- 10 Pull the cord that was originally plugged into the amp all the way out of the factory box.



DU-HA Replacement Audiophile Subwoofer Box for 2004–2008 Ford F-150 SuperCrew *and* for 2006–2008 Lincoln Mark LT

Fits DU-HA Part Numbers
20004
20006

STEP 2

Materials Needed:

- // T20 Torx Bit
- // T15 Torx Bit
- // Original Audiophile Speaker
- // Original Amp
- // Original Wire/Plug



To Install DU-HA Replacement Audiophile Subwoofer Box:

- 1 Feed the speaker wire (*the end with the smaller connectors*) through the hole on the outside of the DU-HA subwoofer box to the inside of the box, leaving the amp plug on the outside. Pull on the speaker wire from inside the speaker box, until plug on the outside of the box is snug.
- 2 Hook the connectors on the wires back to the speaker. (*It doesn't matter which side they hook into.*)
- 3 Set the speaker in the hole. Adjust the speaker so that all 8 holes can be screwed into the wood.
- 4 Put in all 8 existing screws and tighten down using a T20 Torx.
- 5 Plug in the amp plug to the amp.
- 6 Attach the amp to the pre-drilled holes on the side of the subwoofer box as pictured, by inserting the 4 existing screws from the amp box. Tighten using a T15 Torx.
- 7 Install the finished DU-HA replacement subwoofer box inside the DU-HA storage unit under the back seat of the truck. Pull the Ford factory wire (on the floor on the driver's side) over the back of the DU-HA and plug it in to the amp.

