

Installation Instructions

DU-HA Chevrolet/GMC Lock Kit — 99-07 Chevrolet & GMC Silverado/Sierra Extended Cab (Classic)

Fits DU-HA Part Numbers

10001 10048 10002 10049 10003 10050

Materials Needed:

- // Electric Drill
- // 5/16" Drill Bit
- // Hammer
- // Punch

Installation Instructions:

Hole can be drilled on either side, but the passenger side works best, because the channeled hinge on the outside bracket acts as a guide for the bit going through the outside bracket.

- 1 Put seat in latched down position. Press firmly down on bottom of seat to make sure it is down as far as it can go.
- 2 Using a punch and a hammer, mark a groove on the inside seat hinge. Line up punch so that when the hole is drilled it comes through the channel on the outside bracket.
- 3 Using a 5/16" drill bit, press drill in between seat back and seat bottom until it is lined up parallel, as pictured.

 (Note: To make drilling easier, you may use a smaller bit first.)
- Drill through both hinges out towards the door, as pictured.
- Insert key into coupler lock and turn key 1/4 turn to unlock, then gently pull lock to open and release lock pin.

 (Note: You may have to first place the key into the groove next to the key hole, then 'slide' the key over to open the key hole cover to allow the key to go in.)
- 6 Put lock pin through the hole you have just drilled, push lock together, and turn key 1/4 turn to lock.





