

### **Installation Instructions**

# **04-07 Chevrolet & GMC 1500 Light Duty Crew Cab** (Classic) Fits DU-HA Part Number Behind-the-Seat Storage

#### **Materials Needed:**

|| Drill || 1 /2" Drill Bit || Screwdriver

#### **Installation Instructions:**

- 1 Flip the bottom of the back seat up, then fold the seat back down.
- 2 Remove wheel blocks from jack. Loosen jack, then rotate jack so yellow knob faces outward (as pictured) and retighten. Re-attach wheel blocks to jack on opposite side of jack between jack and duct the same way as removed except turn J-bolt over.
- 3 Set the DU-HA in the truck, on top of the ducts with the DU-HA lettering facing forward. Make sure the slot in the front center of the DU-HA is aligned with the center child safety seat bracket.
- Thread nylon strap through each slot on left and right sides of the front of the DU-HA, then through the child safety seat brackets directly above each side (as pictured) to secure the top of the DU-HA. (Note: Screwdriver may be used to feed the strap through the child safety bracket.) Loop strap together by threading up through the bottom of the back slot of the buckle and down through the front slot of the buckle (as pictured). The nylon straps help secure the DU-HA from tipping forward.
- With the DU-HA centered on the ducts, use the DU-HA as a template to mark and drill two 1/2" holes in the ducts. (The ducts are only pressure release vents for cab pressure so a hole will not affect them.)

  Attach one washer and one toggle wing to each bolt, then secure the DU-HA to the ducts by pressing the toggle wing down through the hole in the DU-HA and down through the hole in the duct. Pull up on the DU-HA to apply pressure on the toggle wing and tighten the bolt using a screwdriver.

If desired, install the foam organizer/gun racks by bending and snapping them into the channel slots in the DU-HA. Gun racks can be installed to hold two guns or one gun depending on how you install them.

## **Safety Instructions:**

Warning: Seat back must be latched up at all times while vehicle is moving. Make sure the DU-HA is secured in the vehicle according to installation instructions. Do not store explosives or hazardous materials in the DU-HA. Do not place loaded guns in the DU-HA. For further instructions refer to truck owners manual or contact DU-HA, Inc.







Remove wheel blocks from jack, ther loosen iack.



Rotate jack so yellow knob faces outward (as pictured).





Ribs on buckle should face up. Thread strap through buckle as shown.



2 extra straps are included to secure guns/ gear in place.

